

Declaration of Performance

(according to regulation EU No 305/2011)

DoP No. 00186217-10-2018

- 1) Code of the product type: 1.0038 according to EN 10027-2
- 2) Type: coils & sheets (+ N) **S235JRC** according to EN 10025-2-2004

Intended use of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

To be used in welded, bolted and riveted structures

3) PAO Severstal

162608, Russia, Vologda region, Cherepovets, Mira str., 30


System of assessment and verification of constancy of performance of the product: System 2+ (according to certificate)

Notified factory production control certification body No. 0038 LRV performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control № 0038/CPR/SPB/666869.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in the table.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Technical Development
and Quality Director



P.A. Mishnev

Date: « 29 » 12 2018.



T: +7 (8202) 53 09 00
F: +7 (8202) 53 09 15
severstal@severstal.com
www.severstal.com



А.А. Лысенко
29 АЕК 2018



Essential characteristic		Performance		Harmonised technical specification
Tolerances on dimension and shape	Sheet / coil	EN 10048, EN 10051, EN 10029		EN 10025-1:2004
	Nominal thickness, (mm)	Values, (MPa)		
Yield strength	≤ 15	235		
	Nominal thickness, (mm)	Values, (MPa)		
Tensile strength	< 3	360 + 510		
	≥ 3 ≤ 15			
	Nominal thickness, (mm)	Values, (%)		
Elongation	≤ 1	17		
	> 1 ≤ 1,5	18		
	> 1,5 ≤ 2	19		
	> 2 ≤ 2,5	20		
	> 2,5 ≤ 3	21		
	> 3 ≤ 15	26		
Impact strength(+20 °C)	Nominal thickness, (mm)	Values, (J)		
	≤ 15	27		
Equivalent carbon content (weldability)	Nominal thickness, (mm)	Values, (%)		
	≤ 15	0,35		
Durability (chemical composition)	Nominal thickness, (mm)	Values, (%)		
		≤ 15	C : 0,17	Mn : 1,40; P : 0,035;
		C : 0,20	S: 0,035; N: 0,12; Cu: 0,55	

Declaration of Performance

(according to regulation EU No 305/2011)

DoP No. 00186217-10-2018

1) Code of the product type: 1.0114 according to EN 10027-2

2) Type: coils & sheets (+ N) **S235J0C** according to EN 10025-2-2004

Intended use of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

To be used in welded, bolted and riveted structures

3) PAO Severstal

162608, Russia, Vologda region, Cherepovets, Mira str., 30


System of assessment and verification of constancy of performance of the product: System 2+ (according to certificate)

Notified factory production control certification body No. 0038 LRV performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control № 0038/CPR/SPB/666869.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in the table.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Technical Development
and Quality Director



P.A. Mishnev

Date: «29» 12 2018.

STAMP HERE



29 DEK 2018

Д.А. Лысенко



Essential characteristic		Performance	Harmonised technical specification
Tolerances on dimension and shape	Sheet / coil	EN 10048, EN 10051, EN 10029	EN 10025-1:2004
Yield strength	Nominal thickness, (mm)	Values, (MPa)	
	≤ 15	235	
Tensile strength	Nominal thickness, (mm)	Values, (MPa)	
	< 3	360 + 510	
	≥ 3 ≤ 15		
Elongation	Nominal thickness, (mm)	Values, (%)	
	≤ 1	15	
	> 1 ≤ 1,5	16	
	> 1,5 ≤ 2	17	
	> 2 ≤ 2,5	18	
	> 2,5 ≤ 3	19	
Impact strength(0 °C)	Nominal thickness, (mm)	Values, (J)	
	≤ 15	27	
Equivalent carbon content (weldability)	Nominal thickness, (mm)	Values, (%)	
	≤ 15	0,35	
Durability (chemical composition)	Nominal thickness, (mm)	Values, (%)	
	≤ 15	C : 0,17; Mn : 1,40; P : 0,030; S : 0,030; N : 0,12; Cu : 0,55	